Premium Series

setting the standard in quality and performance

00000

1/2 H.P

chain drive 1/2 HP garage door opener

3265

enhanced style... rugged...reliable

A powerful 1/2 HP motor combined with industrial-strength chain drive provides steady performance and lifting power.



Controls your garage door and turns opener lights on/off from inside garage. Locks out all outside radio signals while you're away. Includes an adjustable light timer and an illuminated oversized push button for convenience.

Security+® 3-button remote control

With rolling code technology, you are assured of a new code with every use. Every time you push the button, the code automatically rolls over to any one of over 100-billion new codes, never to be repeated. Operates up to 3 garage doors.



LEGIMANTE SECTION AND THE PROPERSION AND THE PROPER

features that make a difference

brighter light...better control

200 watts of light. 11/2 to 41/2 minute delay setting control. Plus, hinged lens allows easier bulb replacement.





exclusive! The Smart Garage Door Opener®

Lets you electronically program security codes from the multi-function control panel or the powerhead.



Push-in wiring for guicker installation.



LIFETIME MOTOR WARRANTY

all the safety you **need**



The Protector System®*

Projects an invisible light beam across garage door opening. If anything interrupts the beam while the door is closing, door automatically reverses before making contact. If beam is obstructed, door will not close.

equipped with PosiLock®

Once your garage door goes down, it's securely locked with PosiLock®, a patented Chamberlain® feature. An intruder cannot gain access.





manual release handle

In a power failure, this feature releases the garage door for manual operation.

The in-vehicle universal remote control. See your automobile dealer for availability



enhance your lifestyle with optional accessories

enter

without a key

Open your garage door without using a remote control and close with just the push of a button. Also can be programmed with a temporary entry code for friends and service people.



know for sure the door is closed

Lets you know whether the garage door is open or closed from any room in the house. A flashing red light shows the door is open; a glowing green light indicates the door is closed.

garage door monitor



walk into a

bright garage

It sees you coming! Turns garage door opener lights on automatically when you enter the garage.

premium motion-detecting control panel



park perfectly

every time

The high-tech solution that helps you park perfectly in your garage! As you pull into your garage the laser is activated and projected onto your dashboard, making it easy to park in the same spot every time.

laser garage parking assist



CHAMBERLAIN PROFESSIONAL

World's #1 Installed Garage Door Opener THE CHAMBERLAIN GROUP, INC 845 Larch Avenue • Elmhurst, IL 60126

www.liftmaster.com









I.C./F.C.C. Certified

©2006 LM 3265 07/06 The Chamberlain Group, Inc. Printed in U.S.A.

LMCA3265

MOTOR

Horsepower: 1/2 RPM: 1,625 Thermal Protection: Automatic

DRIVE MECHANISM

Drive Means: Full Chain Reduction Means: Gear 16:1 Door Linkage: Adjustable Door Arm

LOGIC TYPE

Solid-State Microcontroller with Built-in Surge Suppressor

DIMENSIONS

Installed Length: 128" Maximum Door Opening: 7' 6"*
Travel Rate: Approximately 7"/Second Headroom Clearance Required: 2" *Up to 10' with optional 8' or 10' rails.

SHIPPING WEIGHT

Head: 28 lbs. Rail: 17 lbs.

ADJUSTMENTS

Force: Independent External Up and Down

ELECTRICAL

Voltage: 120VAC, 60Hz Wattage: 540 Current Rating: 4.5 UL Listings: Yes Length of Line Cord: 4' (3-prong)

SECURITY+® RADIO CONTROLS

Coding System: Smart Receive Code Button and Indicator Light Operating Range: 150' Approximately Operating Temperature: -40°F to 150°F 3-Volt Lithium Battery (Remote Control) Frequency: 315MHz 373LM 3-Button Remote Security+® Anti-Burglary Coding

LIGHTING SYSTEM

Number of Bulbs: 2 Maximum Wattage: 100 x 2 Length of Light Delay: Adjustable Type of Light Delay: Solid-State

CONVENIENCE/SAFETY

The Protector System Emergency/Quick Release Automatic Trolley Reconnect Ventilation/Pet Opening Down Safety Reverse Up Safety Stop Door Open/Beam Broken/Lights On Program Remote from Multi-Function Control Panel Open/Close/Stop Door from 373LM Remote

MATERIALS

Chassis: Steel Rail: Solid-Steel T Trolley: Steel

CARTONS

Number of Cartons: 2 Carton 1 Dimensions: 20" x 12" x 10" Carton 1 Contents: Multi-Function Control Panel, 373LM Remote, Garage Door Opener Head. The Protector System® Carton 2 Dimensions: 10' 4" x 5" x 5" Carton 2 Contents: Assembled

Solid-Steel T-Rail

*WARNING: Garage doors and openers can be dangerous if not properly installed, tested and operated. Children should be supervised by an adult whenever in or around the garage area.

Lifetime Motor Warranty.

1 year on all other parts. For more information, refer to owner's manual. LiftMaster® garage door openers meet all current state and federal regulations and UL safety regulations as of date of manufacture.