
ELITE SERIES

3850

DC Motor Belt Drive Garage Door Opener with







WITH EVERCHARGE™ BATTERY BACKUP BUILT IN.

For a higher level of security and uninterrupted convenience, we offer a garage door opener that continues working, even when the power goes out.

The EverCharge $^{\text{TM}}$ Battery Backup System will operate the garage door opener for 40 cycles within a 24-hour period and recharges automatically when the power comes back on.



12V DC battery fits neatly inside the opener

Plus, it's the only opener with our patented EverCharge $^{\text{TM}}$ Battery Backup System built right in.

Ultra-quiet DC belt drive system. Variable speed soft start/soft stop. Audible signal tells you the power is out and EverCharge $^{\text{TM}}$ battery is in use.

- 200-watt lighting
- Meets all UL325 requirements
- Lifetime motor and belt warranty

LiftMaster® 3850, the only professionally installed opener with fully integrated EverCharge™ Battery Backup.

At Chamberlain, safety is a major part of our mission.

It's our commitment to you and, quite simply, the way we produce products every day. Our LiftMaster® products are designed to move the largest door in your home, safely, securely and by always putting safety first.

ACCESSORIES INCLUDED



Innovative design automatically streams brilliant blue lights from the push-button windows when you pass your hand over the remote.



Displays time, temperature and diagnostic messages in 3 languages. A motion sensor turns opener lights on "hands-free" and a convenient "learn" button easily programs remotes.

CHAMBERLAIN®
LiftMaster

UNSURPASSED SAFETY AND SECURITY

All LiftMaster® garage door openers are manufactured with the highest level of safety and monitoring systems to ensure safe operation.

- The Protector System® safety sensors reverse the door automatically if the infrared beam is broken, before contact is made.
- Patented technology detects when a door spring breaks and triggers the motor to reverse the door to the full open position.
- Sensing technology will stop the door from closing if contact is made with a person or object.
- Security+® Rolling Code Technology assures a new code is sent every time the remote is used.
- Patented PosiLock® system ensures the door remains securely locked when it is closed.
- Opener light turns on automatically when The Protector System® safety infrared beam is broken.

ENHANCE YOUR LIFESTYLE WITH OPTIONAL ACCESSORIES



know for sure the door is closed

Lets you know whether the garage door is open or closed from any room in the house. A flashing red light shows the door is open; a glowing green light indicates the door is closed.

GARAGE DOOR MONITOR (915LM)

enter without a key

Open your garage door without using a remote control and close with just the push of a button. Also can be programmed with a temporary entry code for friends and service people.





access on the go

Operates up to 3 garage doors. Turns garage door opener lights on and off. Fits on keychain or in a pocket or purse.

MINI 3-BUTTON REMOTE CONTROL with SECURITY+® (370LM)

put control where you want it

For people who want a second control in their garages. A light control button turns garage door opener lights on and off. Auxiliary button can be programmed to open and close a second garage door.



WIRELESS CONTROL PANEL (378LM)



park perfectly every time

The high-tech solution that helps you park perfectly in your garage! As you pull into your garage the laser is activated and projected onto the dashboard, making it easy to park in the same spot every time.

LASER GARAGE PARKING ASSIST (975LM)

STANDARD SPECIFICATIONS

DIMENSIONS

Installed Length: 125"
Maximum Door Opening: 7' 6"*
Headroom Clearance Required: 2"
*Up to 10' with optional 8' or 10' rails

Number of Cartons: 3 Carton 1 Dimensions and Contents: 20" x 11.88" x 9.69" Smart Control Panel™ 373P Premium 3-Button Remote Control Garage Door Opener Head The Protector System®

Carton 2 Dimensions and Contents:

10' 4" x 5" x 5"

Assembled Solid-Steel T-Rail
Carton 3 Dimensions and Contents:

5.31" x 4.63" x 5.13"

485LM EverCharge™ Battery

SECURITY+® RADIO CONTROLS

Coding System: Smart Receiver
Code Button and Indicator Light
373P Premium 3-Button Remote Control
Operating Range: 150' (approximately)
Operating Temperature: -40°F to 150°F
Frequency: 315MHz Frequency: 315MHz Security+® Anti-Burglary Coding

CONVENIENCE/SAFETY

The Protector System® Emergency/Quick Release Automatic Trolley Reconnect Ventilation/Pet Opening Down Safety Reverse Up Safety Stop Door Open/Beam Obstructed/Lights On Program Remote Controls from Smart Control Panel™ EverCharge™ Battery System

ELECTRICAL SPECIFICATIONS

Voltage: 120V AC, 60Hz; Wattage: 524 Total System (including lights); Current Rating: 2.7A; UL Listings: Yes; Length of Line Cord: 6' (3-prong)

LOGIC TYPE

Solid-State Microcontroller with Built-in Surge Suppressor

Number of Bulbs: 2 Maximum Wattage: 100 x 2 Adjustable Time, Solid-State Delay

MECHANICAL SPECIFICATIONS

800 Newtons; 12V DC Motor; RPM: 53 Thermal Protection: Automatic Lubrication: Permanent

DRIVE MECHANISM

Drive Means: Full Reinforced Drive Belt Reduction Means: Gear 63:1 Door Linkage: Adjustable Door Arm

ADJUSTMENTS

Force: Electronic/Internal Auto Force Limit: Internal/Electronic

TRAVEL RATE

Approximately 11" per Second (Up Direction)
Approximately 7.5" per Second (Down Direction)

SHIPPING WEIGHTS

Head: 17.85 Lbs. Rail: 17 Lbs. Battery Backup: 3.9 Lbs.

MATERIALS

Chassis: Steel Rail: Solid-Steel T

LIFETIME MOTOR & BELT WARRANTY

5 years on all other parts. For more information, refer to owner's manual. LiftMaster¹⁸ garage door openers meet all current state and federal regulations and UL safety regulations as of date of manufacture. 1-Year Warranty on 485LM Battery.



The in-vehicle universal remote control. See your automobile dealer for availability.



World's #1 Installed Garage Door Opener THE CHAMBERLAIN GROUP, INC.

845 Larch Avenue • Elmhurst, IL 60126 www.liftmaster.com











©2007 LM 3850 06/07 The Chamberlain Group, Inc. Printed in U.S.A.