ELITE SERIES





SPACE-SAVING WALL-MOUNTED JACKSHAFT.

When you need to save space or have an oversized door or cathedral ceiling, the 3800 is a perfectly engineered solution to wall-mounted jackshaft openers.

The 3800 is mounted to the wall beside the garage door, so ceiling space is freed up for maximum storage. A remote light can be positioned anywhere in the garage and provides 200 watts of bright light wherever it is needed. The powerful 24V DC motor provides ultra-quiet operation, along with variable speed smooth start and smooth stop.

- Cable tension monitor eliminates cable throw; ideal for limited height, cathedral or obstructed ceiling installations
- Power door lock for extra security; when the door is down it is securely locked
- 200-watt lighting via remote light
- Meets all UL325 requirements
- Lifetime motor warranty

LiftMaster[®] 3800, the only professionally installed residential jackshaft opener with optional EverCharge[™] Battery Backup

At Chamberlain, safety is a major part of our mission. It's our commitment to you and, quite simply, the way we produce products every day. Our LiftMaster[®] products are designed to move the largest door in your home, safely, securely and by always putting safety first.

ACCESSORIES INCLUDED



Premium Remote Innovative design automatically streams brilliant blue lights from the push-button windows when you pass your hand over the remote.



Smart Control Panel™ Displays time, temperature and diagnostic messages in 3 languages. A motion sensor turns opener lights on "hands-free" and a convenient "learn" button easily programs remotes.



573(0)()

UNSURPASSED SAFETY AND SECURITY

All LiftMaster® garage door openers are manufactured with the highest level of safety and monitoring systems to ensure safe operation.

- The Protector System[®] safety sensors reverse the door automatically if the infrared beam is broken, before contact is made.
- Patented technology detects when a door spring breaks and triggers the motor to reverse the door to the full open position.
- Sensing technology will stop the door from closing if contact is made with a person or object.
- Security +[®] Rolling Code Technology assures a new code is sent every time the remote is used.
- Patented PosiLock[®] system ensures the door remains securely locked when it is closed.
- Opener light turns on automatically when The Protector System® safety infrared beam is broken.

ENHANCE YOUR LIFESTYLE WITH OPTIONAL ACCESSORIES



know for sure the door is closed

Lets you know whether the garage door is open or closed from any room in the house. A flashing red light shows the door is open; a glowing green light indicates the door is closed.

GARAGE DOOR MONITOR (915LM)

enter without a key

Open your garage door without using a remote control and close with just the push of a button. Also can be programmed with a temporary entry code for friends and service people.



WIRELESS KEYLESS ENTRY with SECURITY +®(377LM)



the door goes up when the power goes out If the power goes out, the battery backup system will operate the garage door opener for 20 full cycles within a 24-hour period.

EVERCHARGE[™] BATTERY BACKUP SYSTEM (475LM)

put control where you want it

For people who want a second control in their garages. A light control button turns garage door opener lights on and off. Auxiliary button can be programmed to open and close a second garage door.



WIRELESS CONTROL PANEL (378LM)



park perfectly every time

The high-tech solution that helps you park perfectly in your garage! As you pull into your garage the laser is activated and projected onto the dashboard, making it easy to park in the same spot every time.

LASER GARAGE PARKING ASSIST (975LM)

SPECIFICATIONS

STANDARD SPECIFICATIONS DIMENSIONS

DIMENSIONS Garage Door Opener Dimensions: 6.85"D x 16.25"H x 6.01"W Maximum Door Size: Up to 14' High, Total of 180 Square Feet Maximum Door Weight: 650 Lbs.

Headroom Clearance Required: 3' from Center of Torsion Bar

CARTONS

Number of Cartons: 1 Carton Dimensions and Contents: 24" × 10" × 12" Smart Control Panel™ 373P Premium 3-Button Remote Control Garage Door Opener Head Power Door Lock Cable Tension Monitor Remote Light The Protector System®

SECURITY +® RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light 373P Premium 3-Button Remote Co Operating Temperature.: -30°F to 150°F Frequency: 315MHz Security+[®] Anti-Burglary Coding

CONVENIENCE/SAFETY

The Protector System[®] Emergency/Quick Release Ventilation/Pet Opening Down Safety Reverse Up Safety Stop Door Open/Beam Obstructed/Lights On Program Remote Controls from Smart Control Panel[™] EverCharge[™] Battery System Compatible Model 475LM (optional accessory)

ELECTRICAL SPECIFICATIONS POWER

Powerkead Voltage: 120V AC, 60Hz; Wattage: 120; Current Rating: 1.0A; UL Listings: Yes; Length of Line Cord: 6' (3-prong); Worklight Voltage: 120V AC, 60Hz; Wattage: 200; Current Rating: 1.7A; UL Listings: Yes; Length of Line Cord: 6' (2-prong)

LOGIC TYPE Solid-State Microcontroller with Built-in Surge Suppressor

LIGHTING Number of Bulbs: 2 Maximum Wattage: 100 x 2 Adjustable Time, Solid-State Delay

MECHANICAL SPECIFICATIONS

MOTOR Heavy-Duty 24V DC Motor 180 Newtons in Up Direction 120 Newtons in Down Direction Thermal Protection: Automatic Lubrication: Permanen

DRIVE MECHANISM Drive Means: Internal Chain and Sprocket Reduction Means: Gear 63:1

ADJUSTMENTS Force: Electronic/Internal Auto Force Limit: Internal/Electronic

TRAVEL RATE nately 7.6" per Second SHIPPING WEIGHT Entire System: 31 Lbs

MATERIALS Plastic Cover

LIFETIME MOTOR WARRANTY

5 years on all other parts. For more information, refer to owner's manual. LiftMaster[®] garage door openers meet all current state and federal regulations and UL safety regulations as of date of manufacture. 1-year warranty on optional battery.



The in-vehicle universal remote control. See your auto dealer for availability.



World's #1 Installed Garage Door Opener THE CHAMBERLAIN GROUP, INC. 845 Larch Avenue • Elmhurst, IL 60126 www.liftmaster.com





©2007 LM 3800 06/07 The Chamberlain Group, Inc. Printed in U.S.A.